

滚花螺母

钢 / 不锈钢, 高位型

规格

钢制款式

- 性能等级 5
- 可视表面精车
- 发黑处理
- 镀锌, 蓝钝处理 ZB

不锈钢款式





- AISI 303 NI
- AISI 316L A4
- 亚光喷砂饰面

信息

滚花螺母 DIN 466 适用于普遍应用, 并且不借助工具就能被旋紧或松开。DIN标准定义之外的M12螺纹螺母也是可购得的。

技术信息

- 不锈钢特性 (参见页 A26)
- 螺栓强度值 / 螺母 (参见页 A20)



DIN 466-ST

说明	d1	d2	d3	h	k	⚖️
DIN 466-M2	M 2	9	4.5	5.3	2	2
DIN 466-M2,5	M 2.5	11	5	6.5	2.5	3
DIN 466-M3	M 3	12	6	7.5	2.5	4
DIN 466-M4	M 4	16	8	9.5	3.5	6
DIN 466-M5	M 5	20	10	11.5	4	12
DIN 466-M6	M 6	24	12	15	5	20
DIN 466-M8	M 8	30	16	18	6	44
DIN 466-M10	M 10	36	20	23	8	84
DIN 466-M12	M 12	40	22	25	10	120

DIN 466-ZB

说明	d1	d2	d3	h	k	⚖️
DIN 466-M2-ZB	M 2	9	4.5	5.3	2	1
DIN 466-M2,5-ZB	M 2.5	11	5	6.5	2.5	2
DIN 466-M3-ZB	M 3	12	6	7.5	2.5	3
DIN 466-M4-ZB	M 4	16	8	9.5	3.5	7
DIN 466-M5-ZB	M 5	20	10	11.5	4	12
DIN 466-M6-ZB	M 6	24	12	15	5	22
DIN 466-M8-ZB	M 8	30	16	18	6	42
DIN 466-M10-ZB	M 10	36	20	23	8	84
DIN 466-M12-ZB	M 12	40	22	25	10	119

DIN 466-SST

STAINLESS STEEL

说明	d1	d2	d3	h	k	⚖️
DIN 466-M2-NI	M 2	9	4.5	5.3	2	3
DIN 466-M2,5-NI	M 2.5	11	5	6.5	2.5	2
DIN 466-M3-NI	M 3	12	6	7.5	2.5	3
DIN 466-M4-NI	M 4	16	8	9.5	3.5	6
DIN 466-M5-NI	M 5	20	10	11.5	4	12
DIN 466-M6-NI	M 6	24	12	15	5	22
DIN 466-M8-NI	M 8	30	16	18	6	40
DIN 466-M10-NI	M 10	36	20	23	8	84
DIN 466-M12-NI	M 12	40	22	25	10	115
DIN 466-M3-A4	M 3	12	6	7.5	2.5	3
DIN 466-M4-A4	M 4	16	8	9.5	3.5	7
DIN 466-M5-A4	M 5	20	10	11.5	4	13
DIN 466-M6-A4	M 6	24	12	15	5	24
DIN 466-M8-A4	M 8	30	16	18	6	91
DIN 466-M10-A4	M 10	36	20	23	8	125