

磁体

硬铁素体/钕铁硼, 钢制外壳, 带螺杆

规格

磁铁

- 硬铁 **HF**
工作温度高达 200 °C
- NdFeB **ND**
钕铁硼
工作温度高达 80 °C
- NdFeB **NDT**
钕铁硼
工作温度高达 150 °C

外壳

钢制, 镀锌

信息


GN 50.3 固定磁体与钢外壳和塑料环组合成一个系统, 保护和增强磁体, 确保磁通量到磁性表面的最佳传输。

附件


- GN 70 固定盘 (参见页 2051)
- GN 70.1 附着盘片 (参见页 2051)
- GN 70.2 橡胶帽 (参见页)

技术信息

- 固定磁体的更详细信息 (参见页 2022)



附着面俯视图



GN 50.3

说明	d ₁	d ₂	h	长度 l	标称磁力以 N	△
GN 50.3-HF-10-M3	10 ±0.1	M3	4.5 +0.2/-0.1	7	4	2
GN 50.3-HF-13-M3	13 ±0.1	M3	4.5 +0.2/-0.1	7	10	3
GN 50.3-HF-16-M3	16 ±0.1	M3	4.5 +0.2/-0.1	7	18	5
GN 50.3-HF-16-M4	16 ±0.1	M4	4.5 +0.2/-0.1	6	18	5
GN 50.3-HF-20-M3	20 ±0.1	M3	6 +0.2/-0.1	7	30	10
GN 50.3-HF-25-M4	25 ±0.1	M4	7 +0.3/-0.2	8	40	19
GN 50.3-HF-25-M6	25 ±0.1	M6	7 +0.3/-0.2	20	40	22
GN 50.3-HF-32-M4	32 ±0.1	M4	7 +0.3/-0.2	8	80	32
GN 50.3-HF-32-M6	32 ±0.1	M6	7 +0.3/-0.2	12	80	31
GN 50.3-HF-32-M8	32 ±0.1	M8	7 +0.3/-0.2	10	80	32
GN 50.3-HF-47-M6	47 ±0.1	M6	9 +0.5/-0.2	8	180	85
GN 50.3-HF-57-M6	57 ±0.1	M6	10.5 +0.5/-0.2	8	280	146
GN 50.3-HF-63-M6	63 ±0.1	M6	14 +0.5/-0.2	15	350	233
GN 50.3-HF-80-M8	80 ±0.1	M8	10 +0.5/-0.2	13	600	269
GN 50.3-ND-6-M3	6 ±0.1	M3	4.5 ±0.1	7	5	1
GN 50.3-ND-8-M4	8 ±0.1	M4	4.5 ±0.1	8	13	2
GN 50.3-ND-10-M3	10 ±0.1	M3	4.5 ±0.1	7	25	2
GN 50.3-ND-10-M4	10 ±0.1	M4	4.5 ±0.1	8	25	3
GN 50.3-ND-13-M5	13 ±0.1	M5	4.5 ±0.1	8	60	6
GN 50.3-ND-16-M4	16 ±0.1	M4	4.5 ±0.1	8	85	7
GN 50.3-ND-16-M6	16 ±0.1	M6	4.5 ±0.1	8	95	8
GN 50.3-ND-20-M6	20 ±0.1	M6	6 ±0.1	10	140	16
GN 50.3-ND-25-M6	25 ±0.1	M6	7 ±0.2	10	200	28
GN 50.3-ND-32-M6	32 ±0.1	M6	7 ±0.2	10	350	43
GN 50.3-ND-40-M8	40 ±0.1	M8	8 ±0.2	12	670	80
GN 50.3-ND-47-M8	47 ±0.1	M8	9.2 ±0.2	13	790	107
GN 50.3-NDT-10-M4	10 ±0.1	M4	4.5 ±0.1	8	33	4
GN 50.3-NDT-13-M5	13 ±0.1	M5	4.5 ±0.1	8	75	6
GN 50.3-NDT-16-M6	16 ±0.1	M6	4.5 ±0.1	8	110	8
GN 50.3-NDT-20-M6	20 ±0.1	M6	6 ±0.1	10	172	16
GN 50.3-NDT-25-M6	25 ±0.1	M6	7 ±0.2	10	233	28
GN 50.3-NDT-32-M6	32 ±0.1	M6	7 ±0.2	10	400	41

