

T形螺母

铝型材系统配件

规格

钢制
镀锌, 蓝钝处理

信息

GN 507 型T形螺母专门设计用于压铝轨道上。
可从T形槽的任一端插入。



菱形T形槽螺母

规格

热处理钢
- 拉伸强度等级10
- 发黑处理

信息






GN 508.1 菱形T形槽螺母可垂直插入T形槽。

技术信息

- 螺母强度值 (参见页 A20)



T形螺母滑入



GN 507

型号	a -0.1/-0.3	d	e1	e2	h	k +0.1	⚖
GN 507-8-M4	8	M 4	16	16	6	4.2	13
GN 507-8-M5	8	M 5	16	16	6	4.2	9
GN 507-8-M6	8	M 6	16	16	6	4.2	8
GN 507-8-M8	8	M 8	16	16	6	4.2	7
GN 507-10-M4	10	M 4	20	19.5	10.5	5.5	19
GN 507-10-M5	10	M 5	20	19.5	10.5	5.5	18
GN 507-10-M6	10	M 6	20	19.5	10.5	5.5	15
GN 507-10-M8	10	M 8	20	19.5	10.5	5.5	13

GN 508.1

型号	a -0.3/-0.5	d	e -0.5	h	k -0.5	DIN 650 T形槽 宽度	⚖
GN 508.1-8-M6	8	M 6	13	10	6	8	5
GN 508.1-10-M8	10	M 8	15	12	6	10	9
GN 508.1-12-M10	12	M 10	18	14	7	12	13
GN 508.1-14-M12	14	M 12	22	16	8	14	23
GN 508.1-16-M14	16	M 14	25	18	9	16	32
GN 508.1-18-M16	18	M 16	28	20	10	18	44
GN 508.1-22-M20	22	M 20	35	28	14	22	97

