












铰接夹				
标准	属性	动力学	F夹紧力为6 bar	以N计的夹持能力
GN 860 (参见页 1614)	- 曲杆原理 - 张紧机构在设计上与手动操作的铰接夹相对应 - 末端位置检测		380...3200	700...4000
GN 861 (参见页 1613)	- 曲杆原理 - 具有高夹紧力的重型设计 - 末端位置检测		2500...3600	10000...20000
GN 862 (参见页 1616)	- 曲杆原理 - 经由斜角基座安装 - 末端位置检测		570...1800	750...2600
GN 962 (参见页)	- 曲杆原理 - 经由斜角基座安装 - 具有高夹紧力的重型设计 - “长使用寿命” - 末端位置检测		870...2280	2200...8500
GN 862.1 (参见页 1618)	- 曲杆原理 - 经由斜角基座安装 - 设计和尺寸与GN 862相同, 但需额外手动操作 - 末端位置检测		1260...1800	2200...2600
GN 863 (参见页 1620)	- 曲杆原理 - 经由斜角基座安装 - 具有高夹紧力的重型设计 - 末端位置检测		3250...5600	10000...20000
GN 890 (参见页 1621)	- 曲杆原理 - 张紧机构在设计上与手动操作的推拉力型铰接夹相对应 - 用于推进夹紧 - 末端位置检测		780...5520	1200...25000

强力夹				
标准	属性	动力学	F夹紧力为6 bar	以N计的夹持能力
GN 864 (参见页 1634)	- 死点机构 - 水平、垂直或对中夹紧臂 - 高夹紧力 - 体积小巧 - 空气消耗低 - 长使用寿命 - 末端位置检测		2220...9000	4070...13300
GN 865 (参见页 1635)			1250...4900	2300...7200
GN 866 (参见页 1636)			630...1800	1150...2000
强力夹				
标准	属性	动力学	F夹紧力为6 bar	以N计的夹持能力
GN 8620 (参见页)	- 曲杆原理 - 通过螺纹表面进行安装 - 末端位置检测		530...2700	800...10410
GN 8621 (参见页)	- 设计和尺寸与 GN 8620 相同, 但增加了一个手动驱动装置		530...2700	800...10410





摆动夹				
标准	属性	动力学	F夹紧力为6 bar	以N计的夹持能力
GN 875 (参见页)	- 枢转和线性运动 - 在块版本中, 具有通用安装能力 - 体积小巧 - 末端位置检测		170...1100	170...1100
GN 876 (参见页)	- 枢转和线性运动 - 带旋入式螺纹, 可调节 - 体积小巧		170...1100	170...1100