













Tables of the possible combinations Bases / Stem

		Base L.S.A				Base L.V.A				Base L.V.F				Base L.V.F.O												
Base	d ₂	d ₂ 2		d ₂ 14		d ₂ 14		d ₂ 24		d ₂ 14		d ₂ 24		d ₂ 14		d ₂ 14		d ₂ 14								
		D	1	25	32	40	50	25	32	40	50	60	70	80	100	125	80	100	80	100	125	60	80			
SM. zinc-plated steel stem	d ₂ 2	d ₂ 1	d x l 3	Max limit static load [N]	5000	6000	7000	7000	7000	10000	12000	12000	18000	18000	20000	23000	23000	28000	30000	20000	18000	23000	28000	30000	14000	16000
	 $d_2 = \varnothing 14$	M8x43÷68						•	•	•	•	•	•	•	•	•	•	•			•	•				
		M10x43÷68÷98						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
		M12x43÷68÷98						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
		M16x68÷108÷148÷168						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
	 $d_2 = \varnothing 24$	M16x58÷98÷138÷158													•	•	•	•	•	•	•	•	•			
		M20x98÷138÷158÷198													•	•	•	•	•	•	•	•	•			
		M24x98÷158÷198													•	•	•	•	•	•	•	•	•			
	 $d_2 = \varnothing 14$	M8x43÷68						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
		M10x43÷68÷98						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
		M12x43÷68÷98						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
		M16x68÷108÷148÷168						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
	 $d_2 = \varnothing 24$	M16x58÷98÷138÷158													•	•	•	•	•	•	•	•	•			
		M20x98÷138÷158÷198													•	•	•	•	•	•	•	•	•			
		M24x98÷158÷198													•	•	•	•	•	•	•	•	•			
	 $d_2 = \varnothing 8.5$	M8x48÷73	•	•	•	•																				
		M10x48÷73÷103	•	•	•	•																				
		M12x48÷73÷103	•	•	•	•																				
	 $d_2 = \varnothing 14$	M16x68÷108÷148÷168					•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
		M20x110÷150÷170÷210					•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
		M24x110÷170÷210					•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
DESCRIPTION STRUCTURE																										
		Levelling element			Base diameter (D)			Articulation diameter (d ₂)	To add only for the version with no-slip disk assembled to the base		To add only for the version with stainless steel stem		Thread diameter (d) Thread length (l)		To add only for the version with antistatic base											
		LV.A	-	80	-	14	-	AS	-	SST	-	M8x43	-	ESD-C												
		LV.A	-	80	-	14	-	AS	-		-		-	ESD-C												
		SM	-		14					SST	-	M8x43														