







联轴器

型号概览

标准	轴 Ø 单位 mm	轮毂夹紧	额定扭矩 Nm	倾斜度			零背隙
				轴向	横向	角向	
GN 2240 参见页 6 弹性体夹 爪联轴器	3 - 25		0.7 - 60	X	X	X	
GN 2241 参见页 10 弹性体夹 爪联轴器	3 - 25		0.7 - 60	X	X	X	
GN 2242 参见页 14 联轴器	4 - 20		1 - 28		X	X	
GN 2243 参见页 16 联轴器	2 - 20		0.5 - 28		X	X	
GN 2244 参见页 18 波纹管联 轴器	5 - 19		1.5 - 10	X	X	X	X
GN 2246 参见页 20 横梁联 轴器	4 - 12		0.3 - 4	X	X	X	X

联轴器

型号概览

标准	适用于			应用示例	零背隙	
	伺服电机	步进电机	交直流两用电机			
GN 2240 参见页 6 弹性体夹爪联轴器		X	X	X	- 液压泵 - 包装机器 - 工业机器人 - 风扇 - 搅拌器	- 高扭矩 - 快捷插入式组件
GN 2241 参见页 10 弹性体夹爪联轴器		X	X	X		
GN 2242 参见页 14 联轴器			X	X	- 输送机系统 - 包装机器 - 定位驱动器 - 泵	- 高扭矩 - 高横向倾斜补偿 - 快捷插入式组件
GN 2243 参见页 16 联轴器			X	X		
GN 2244 参见页 18 波纹管联轴器		X	X		- 旋转编码器 - 位置测量系统 - 试验台 - 工业机器人 - 主轴驱动器	- 精确的角度和扭矩传递 - 高抗扭刚度
GN 2246 参见页 20 横梁联轴器			X		- 糖果机 - 工业机器人 - CAT 扫描仪 - 位置测量系统	- 精确的角度和扭矩传递 - 由单体材料制造 - 高抗扭刚度